



# PTP 820G

## Licensed

## Microwave Radio



### Split-Mount, Multi-Carrier Options

### Specifications

#### RADIO

- 6-38 GHz
- 1+0, 1+1 HSB, E/W, 2+0
- 1+1 Unit redundancy (external protection)

#### Radio Features

- Multi-Carrier Adaptive Bandwidth Control (up to 2+0)
- Protection: 1+1 HSB, SD (BBS)
- QPSK to 2048 QAM w/ACM
- 3.5 MHz to 60 MHz channel size
- XPIC

#### ETHERNET

##### Ethernet Interfaces

- Traffic Interfaces – 4 x 10/100/1000Base-T (RJ-45) and 2x1000base-X (SFP), 16 x E1/T1 (Optional MDR 69-pin)
- Management Interface - 2 x 10/100 Base-T (RJ-45)
- External Alarm Interface – 1 x DB9
- SFP Types - Optical 1000Base-LX (1310 nm) or SX (850nm)  
Note: SFP devices must be of industrial grade (-40°C to +85°C)

##### Ethernet Features

- MTU – 9600 Bytes
- Quality of Service
  - Multiple Classification criteria (VLAN ID, p-bits, IPv4, DSCP, IPv6 TC, MPLS EXP)
  - 8 priority queues per port
  - Deep buffering (configurable up to 64 Mbit per queue)
  - WRED
  - P-bit marking/remarking
- 4K VLANs
- VLAN add/remove/translate
- Frame Cut Through – controlled latency and PDV for delay sensitive applications
- Header De-Duplication – Capacity boosting by eliminating inefficiency in all

layers (L2, MPLS, L3, L4, Tunneling – GTP for LTE, GRE)

- Adaptive Bandwidth Notification (ABN)
- Network Resiliency – ERP (G.8032) and Multiple Spanning Tree Protocol (MSTP)
- Ethernet OAM – ITU-T Y.1731 FM

#### SYNCHRONIZATION

##### Synchronization Distribution

- Sync Distribution over any traffic interface (GE/FE)
- Sync-E (ITU-T G.8261, G.8262)
- SSM/ESMC Support for ring/mesh applications (ITU-T G.8264)
- Sync-E Regenerator mode, providing PRC grade (ITU-T G.811) performance for smart pipe applications.

##### IEEE-1588

- Optimized Transport for reduced PDV
- IEEE-1588 Transparent Clock (TC)
- IEEE-1588 Boundary Clock (BC)

#### STANDARD

##### Supported Ethernet Standards

- 10/100/1000base-T/X (IEEE 802.3)
- Ethernet VLANs (IEEE 802.3ac)
- Virtual LAN (VLAN, IEEE 802.1Q)
- Class of service (IEEE 802.1p)
- Provider bridges (QinQ – IEEE 802.1ad)
- Link aggregation (IEEE 802.3ad)
- Auto MDI/MDIX for 1000baseT
- RFC 1349: IPv4 TOS
- RFC 2474: IPv4 DSCP
- RFC 2460: IPv6 Traffic Classes

##### Security

- AES 256-bit Encryption
- Secured protocols (HTTPS, SNMPV3, SSH, SFTP)
- RADIUS authentication and authorization

##### Standards Compliance

- Radio Spectral Efficiency: EN 302 217-2-2
- EMC: EN 301 489-4, EN 301 489-1, FCC 47 CFR, Part15, Class B
- Safety: IEC 60950, EN60950-1, IEC 60950-1, UL60950-1, CSA-C22.2 No.60950-1, EN 60950-22, UL 60950-22, CSA C22.2.60950-22
- Ingress Protection of RFU-C: IP66
- Operation: ETSI EN 300 019-1-3 class 3.2
- Storage: ETSI EN 300 019-1-1 Class 1.2
- Transportation: ETSI EN 300 019-1-2 Class 2.3

#### TECHNICAL SPECIFICATION

##### Mechanical Specifications

- IDU Dimensions – 44mm(H), 426mm(W), 180mm(D), 2.5kg
- RFU-C Dimensions – 200mm (H), 200mm (W), 85mm(D), 4kg

##### Environmental Specifications

- IDU: -5°C to +55°C (-25°C to +65°C extended)
- RFU-C: -33°C to +55°C (-45°C to +60°C extended)

##### Power Input Specifications

- IDU Standard Input: -48 VDC
- IDU DC Input range: -40 to -60 VDC
- RFU-C DC Input range: -40.5 to -59 VDC

##### Power Consumption Specifications

- IDU Eth-only with single modem: 23.5W, addition for second modem, 2.9W, additional for 16 E1/DS1, 11w
- RFU-C: 6-26GHz; 1+0 22W; 1+1 39W; 28-38GHz, 1+0 26W; 1+1 43W

# Specifications

## TRANSMIT POWER

Transmit Power (dBm)	Frequency (GHz)								
	6-8	11-15	18-23	26	28	31	32	36	38
QPSK	26	24	22	21	14	16	18	12	18
8 PSK	26	24	22	21	14	16	18	12	18
16 QAM	25	23	21	20	14	15	17	11	17
32 QAM	24	22	20	19	14	14	16	10	16
64 QAM	24	22	20	19	14	14	16	10	16
128 QAM	24	22	20	19	14	14	16	10	16
256 QAM	22	20	18	17	12	12	14	8	14
512 QAM	22	20	18	17	9	12	14	10	14
1024 QAM	21	19	17	16	8	11	13	9	13
2048 QAM	19	17	15	14	6	9	11	7	11

## RECEIVE SENSITIVITY

Modulation	Channel Spacing	Frequency (GHz)							
		6	7-8	11-15	18	23	26	28	31-38
QPSK	3.5 MHz & 5 MHz	-97.5	-97.0	-97.5	-96.5	-96.0	-95.0	-93.0	-94.0
16 QAM		-91.0	-90.5	-91.0	-90.0	-89.5	-88.5	-86.5	-87.5
32 QAM		-88.0	-87.5	-88.0	-87.0	-86.5	-85.5	-83.5	-84.5
64 QAM		-84.5	-84.0	-84.5	-83.5	-83.0	-82.0	-80.0	-81.0
128 QAM		-81.0	-80.5	-81.0	-80.0	-79.5	-78.5	-76.5	-77.5
256 QAM		-77.5	-77.0	-77.5	-76.5	-76.0	-75.0	-73.0	-74.0
QPSK	7 MHz	-95.0	-94.5	-95.0	-94.0	-93.5	-92.5	-90.5	-91.5
8 PSK		-89.0	-88.5	-89.0	-88.0	-87.5	-86.5	-84.5	-85.5
16 QAM		-88.5	-88.0	-88.5	-87.5	-87.0	-86.0	-84.0	-85.0
32 QAM		-85.0	-84.5	-85.0	-84.0	-83.5	-82.5	-80.5	-81.5
64 QAM		-82.0	-81.5	-82.0	-81.0	-80.5	-79.5	-77.5	-78.5
128 QAM		-79.0	-78.5	-79.0	-78.0	-77.5	-76.5	-74.5	-75.5
256 QAM		-75.5	-75.0	-75.5	-74.5	-74.0	-73.0	-71.0	-72.0
512 QAM		-73.5	-73.0	-73.5	-72.5	-72.0	-71.0	-69.0	-70.0
1024 QAM (strong FEC)		-70.0	-69.5	-70.0	-69.0	-68.5	-67.5	-65.5	-66.5
1024 QAM (light FEC)		-69.5	-69.0	-69.5	-68.5	-68.0	-67.0	-65.0	-66.0
QPSK	10 MHz	-93.5	-93.0	-93.5	-92.5	-92.0	-91.0	-89.0	-90.0
8 PSK		-88.5	-88.0	-88.5	-87.5	-87.0	-86.0	-84.0	-85.0
16 QAM		-87.5	-87.0	-87.5	-86.5	-86.0	-85.0	-83.0	-84.0
32 QAM		-84.0	-83.5	-84.0	-83.0	-82.5	-81.5	-79.5	-80.5
64 QAM		-80.5	-80.0	-80.5	-79.5	-79.0	-78.0	-76.0	-77.0
128 QAM		-77.5	-77.0	-77.5	-76.5	-76.0	-75.0	-73.0	-74.0
256 QAM		-74.5	-74.0	-74.5	-73.5	-73.0	-72.0	-70.0	-71.0
512 QAM		-72.0	-71.5	-72.0	-71.0	-70.5	-69.5	-67.5	-68.5
1024 QAM (strong FEC)		-69.0	-68.5	-69.0	-68.0	-67.5	-66.5	-64.5	-65.5
1024 QAM (light FEC)		-68.0	-67.5	-68.0	-67.0	-66.5	-65.5	-63.5	-64.5
QPSK	14 MHz	-92.0	-91.5	-92.0	-91.0	-90.5	-89.5	-87.5	-88.5
8 PSK		-86.0	-85.5	-86.0	-85.0	-84.5	-83.5	-81.5	-82.5
16 QAM		-85.0	-84.5	-85.0	-84.0	-83.5	-82.5	-80.5	-81.5
32 QAM		-82.0	-81.5	-82.0	-81.0	-80.5	-79.5	-77.5	-78.5
64 QAM		-79.0	-78.5	-79.0	-78.0	-77.5	-76.5	-74.5	-75.5
128 QAM		-75.5	-75.0	-75.5	-74.5	-74.0	-73.0	-71.0	-72.0
256 QAM		-73.0	-72.5	-73.0	-72.0	-71.5	-70.5	-68.5	-69.5
512 QAM		-70.0	-69.5	-70.0	-69.0	-68.5	-67.5	-65.5	-66.5
1024 QAM (strong FEC)		-67.0	-66.5	-67.0	-66.0	-65.5	-64.5	-62.5	-63.5

PTP 820G SPLIT MOUNT SOLUTION SPECIFICATION SHEET

1024 QAM (light FEC)		-66.5	-66.0	-66.5	-65.5	-65.0	-64.0	-62.0	-63.0
		Frequency (GHz)							
Modulation	Channel Spacing	6	7-8	11-15	18	23	26	28	31-38
QPSK	20 MHz	-90.5	-90.0	-90.5	-89.5	-89.0	-88.0	-86.0	-87.0
8 PSK		-85.5	-85.0	-85.5	-84.5	-84.0	-83.0	-81.0	-82.0
16 QAM		-84.0	-83.5	-84.0	-83.0	-82.5	-81.5	-79.5	-80.5
32 QAM		-80.5	-80.0	-80.5	-79.5	-79.0	-78.0	-76.0	-77.0
64 QAM		-77.5	-77.0	-77.5	-76.5	-76.0	-75.0	-73.0	-74.0
128 QAM		-74.5	-74.0	-74.5	-73.5	-73.0	-72.0	-70.0	-71.0
256 QAM		-71.5	-71.0	-71.5	-70.5	-70.0	-69.0	-67.0	-68.0
512 QAM		-69.0	-68.5	-69.0	-68.0	-67.5	-66.5	-64.5	-65.5
1024 QAM (Strong FEC)		-66.0	-65.5	-66.0	-65.0	-64.5	-63.5	-61.5	-62.5
1024 QAM (Light FEC)		-65.0	-64.5	-65.0	-64.0	-63.5	-62.5	-60.5	-61.5
2048 QAM		-61.5	-61.0	-61.5	-60.5	-60.0	-59.0	-57.0	-58.0
QPSK	25 MHz	-90.0	-89.5	-90.0	-89.0	-88.5	-87.5	-85.5	-86.5
8 PSK		-84.5	-84.0	-84.5	-83.5	-83.0	-82.0	-80.0	-81.0
16 QAM		-83.0	-82.5	-83.0	-82.0	-81.5	-80.5	-78.5	-79.5
32 QAM		-79.5	-79.0	-79.5	-78.5	-78.0	-77.0	-75.0	-76.0
64 QAM		-76.5	-76.0	-76.5	-75.5	-75.0	-74.0	-72.0	-73.0
128 QAM		-73.5	-73.0	-73.5	-72.5	-72.0	-71.0	-69.0	-70.0
256 QAM		-70.5	-70.0	-70.5	-69.5	-69.0	-68.0	-66.0	-67.0
512 QAM		-68.0	-67.5	-68.0	-67.0	-66.5	-65.5	-63.5	-64.5
1024 QAM (Strong FEC)		-65.0	-64.5	-65.0	-64.0	-63.5	-62.5	-60.5	-61.5
1024 QAM (Light FEC)		-64.5	-64.0	-64.5	-63.5	-63.0	-62.0	-60.0	-61.0
2048 QAM		-60.5	-60.0	-60.5	-59.5	-59.0	-58.0	-56.0	-57.0
QPSK	28 MHz	-89.0	-88.5	-89.0	-88.0	-87.5	-86.5	-84.5	-85.5
8 PSK		-84.5	-84.0	-84.5	-83.5	-83.0	-82.0	-80.0	-81.0
16 QAM		-82.5	-82.0	-82.5	-81.5	-81.0	-80.0	-78.0	-79.0
32 QAM		-79.0	-78.5	-79.0	-78.0	-77.5	-76.5	-74.5	-75.5
64 QAM		-76.0	-75.5	-76.0	-75.0	-74.5	-73.5	-71.5	-72.5
128 QAM		-72.5	-72.0	-72.5	-71.5	-71.0	-70.0	-68.0	-69.0
256 QAM		-69.5	-69.0	-69.5	-68.5	-68.0	-67.0	-65.0	-66.0
512 QAM		-67.5	-67.0	-67.5	-66.5	-66.0	-65.0	-63.0	-64.0
1024 QAM (Strong FEC)		-64.5	-64.0	-64.5	-63.5	-63.0	-62.0	-60.0	-61.0
1024 QAM (Light FEC)		-63.5	-63.0	-63.5	-62.5	-62.0	-61.0	-59.0	-60.0
2048 QAM		-60.0	-59.5	-60.0	-59.0	-58.5	-57.5	-55.5	-56.5
QPSK	30 MHz	-89.0	-88.5	-89.0	-88.0	-87.5	-86.5	-84.5	-85.5
8 PSK		-83.5	-83.0	-83.5	-82.5	-82.0	-81.0	-79.0	-80.0
16 QAM		-82.0	-81.5	-82.0	-81.0	-80.5	-79.5	-77.5	-78.5
32 QAM		-78.5	-78.0	-78.5	-77.5	-77.0	-76.0	-74.0	-75.0
64 QAM		-75.5	-75.0	-75.5	-74.5	-74.0	-73.0	-71.0	-72.0
128 QAM		-72.5	-72.0	-72.5	-71.5	-71.0	-70.0	-68.0	-69.0
256 QAM		-69.5*	-69.0	-69.5	-68.5	-68.0	-67.0	-65.0	-66.0
512 QAM		-67.5	-67.0	-67.5	-66.5	-66.0	-65.0	-63.0	-64.0
1024 QAM (strong FEC)		-64.0	-63.5	-64.0	-63.0	-62.5	-61.5	-59.5	-60.5
1024 QAM (light FEC)		-63.0	-62.5	-63.0	-62.0	-61.5	-60.5	-58.5	-59.5
2048 QAM		-59.5	-59.0	-59.5	-58.5	-58.0	-57.0	-55.0	-56.0
QPSK	40 MHz	-87.5	-87.0	-87.5	-86.5	-86.0	-85.0	-83.0	-84.0
8 PSK		-82.5	-82.0	-82.5	-81.5	-81.0	-80.0	-78.0	-79.0
16 QAM		-81.0	-80.5	-81.0	-80.0	-79.5	-78.5	-76.5	-77.5
32 QAM		-77.5	-77.0	-77.5	-76.5	-76.0	-75.0	-73.0	-74.0
64 QAM		-74.5	-74.0	-74.5	-73.5	-73.0	-72.0	-70.0	-71.0
128 QAM		-71.5	-71.0	-71.5	-70.5	-70.0	-69.0	-67.0	-68.0
256 QAM		-69.0	-68.5	-69.0	-68.0	-67.5	-66.5	-64.5	-65.5
512 QAM		-66.5	-66.0	-66.5	-65.5	-65.0	-64.0	-62.0	-63.0
1024 QAM (strong FEC)		-63.5	-63.0	-63.5	-62.5	-62.0	-61.0	-59.0	-60.0
1024 QAM (light FEC)		-62.5	-62.0	-62.5	-61.5	-61.0	-60.0	-58.0	-59.0

PTP 820G SPLIT MOUNT SOLUTION SPECIFICATION SHEET

2048 QAM		-59.0	-58.5	-59.0	-58.0	-57.5	-56.5	-54.5	-55.5
		Frequency (GHz)							
Modulation	Channel Spacing	6	7-8	11-15	18	23	26	28	31-38
QPSK	50 MHz	-87.0	-86.5	-87.0	-86.0	-85.5	-84.5	-82.5	-83.5
8 PSK		-81.5	-81.0	-81.5	-80.5	-80.0	-79.0	-77.0	-78.0
16 QAM		-80.0	-79.5	-80.0	-79.0	-78.5	-77.5	-75.5	-76.5
32 QAM		-76.5	-76.0	-76.5	-75.5	-75.0	-74.0	-72.0	-73.0
64 QAM		-73.0	-72.5	-73.0	-72.0	-71.5	-70.5	-68.5	-69.5
128 QAM		-71.0	-70.5	-71.0	-70.0	-69.5	-68.5	-66.5	-67.5
256 QAM		-67.5	-67.0	-67.5	-66.5	-66.0	-65.0	-63.0	-64.0
512 QAM		-65.0	-64.5	-65.0	-64.0	-63.5	-62.5	-60.5	-61.5
1024 QAM (strong FEC)		-62.0	-61.5	-62.0	-61.0	-60.5	-59.5	-57.5	-58.5
1024 QAM (light FEC)		-61.0	-60.5	-61.0	-60.0	-59.5	-58.5	-56.5	-57.5
2048 QAM	56 MHz	-57.5	-57.0	-57.5	-56.5	-56.0	-55.0	-53.0	-54.0
QPSK		-85.5	-85.0	-85.5	-84.5	-84.0	-83.0	-81.0	-82.0
8 PSK		-81.5	-81.0	-81.5	-80.5	-80.0	-79.0	-77.0	-78.0
16 QAM		-79.0	-78.5	-79.0	-78.0	-77.5	-76.5	-74.5	-75.5
32 QAM		-75.5	-75.0	-75.5	-74.5	-74.0	-73.0	-71.0	-72.0
64 QAM		-72.5	-72.0	-72.5	-71.5	-71.0	-70.0	-68.0	-69.0
128 QAM		-69.5	-69.0	-69.5	-68.5	-68.0	-67.0	-65.0	-66.0
256 QAM		-66.5	-66.0	-66.5	-65.5	-65.0	-64.0	-62.0	-63.0
512 QAM		-64.5	-64.0	-64.5	-63.5	-63.0	-62.0	-60.0	-61.0
1024 QAM (strong FEC)		-61.0	-60.5	-61.0	-60.0	-59.5	-58.5	-56.5	-57.5
1024 QAM (light FEC)	-60.0	-59.5	-60.0	-59.0	-58.5	-57.5	-55.5	-56.5	
2048 QAM	60 MHz	-55.5	-55.0	-55.5	-54.5	-54.0	-53.0	-51.0	-52.0
QPSK		-86.0	-85.5	-86.0	-85.0	-84.5	-83.5	-81.5	-82.5
8 PSK		-81.5	-81.0	-81.5	-80.5	-80.0	-79.0	-77.0	-78.0
16 QAM		-79.0	-78.5	-79.0	-78.0	-77.5	-76.5	-74.5	-75.5
32 QAM		-75.5	-75.0	-75.5	-74.5	-74.0	-73.0	-71.0	-72.0
64 QAM		-72.5	-72.0	-72.5	-71.5	-71.0	-70.0	-68.0	-69.0
128 QAM		-69.5	-69.0	-69.5	-68.5	-68.0	-67.0	-65.0	-66.0
256 QAM		-66.5	-66.0	-66.5	-65.5	-65.0	-64.0	-62.0	-63.0
512 QAM		-64.5	-64.0	-64.5	-63.5	-63.0	-62.0	-60.0	-61.0
1024 QAM (strong FEC)		-61.0	-60.5	-61.0	-60.0	-59.5	-58.5	-56.5	-57.5
1024 QAM (light FEC)	-61.0	-60.5	-61.0	-60.0	-59.5	-58.5	-56.5	-57.5	
2048 QAM	-57.0	-56.5	-57.0	-56.0	-55.5	-54.5	-52.5	-53.5	

ETHERNET THROUGHPUT

Modulation	Channel Size	Ethernet Throughput (Mbps)			Channel Size	Ethernet Throughput (Mbps)		
		No Compression	L2 Compression	Multi-Layer Compression		No Compression	L2 Compression	Multi-Layer Compression
QPSK	3.5 MHz & 5 MHz (No XPIC)	3	3-4	4-11	7 MHz (No XPIC)	8	8-10	9-27
8 PSK		8	8-9	9-26		13	13-14	13-40
16 QAM		11	11-13	12-36		18	18-20	19-58
32 QAM		14	14-16	15-45		24	24-27	25-77
64 QAM		17	17-19	18-54		30	30-34	31-95
128 QAM		19	19-22	20-62		36	36-41	37-114
256 QAM		N/A	N/A	N/A		41	41-47	43-132
512 QAM		N/A	N/A	N/A		44	44-50	46-141
1024 QAM (Strong FEC)		N/A	N/A	N/A		47	47-54	49-151

PTP 820G SPLIT MOUNT SOLUTION SPECIFICATION SHEET

1024 QAM (Light FEC)		N/A	N/A	N/A		50	51-57	53-161	
		Ethernet Throughput (Mbps)					Ethernet Throughput (Mbps)		
Modulation	Channel Size	No Compression	L2 Compression	Multi-Layer Compression	Channel Size	No Compression	L2 Compression	Multi-Layer Compression	
QPSK	10 MHz (No XPIC)	12	12-14	13-40	14 MHz (No XPIC)	19	19-22	20-62	
8 PSK		19	19-21	20-61		29	29-33	30-93	
16 QAM		26	26-30	27-83		40	40-45	42-128	
32 QAM		34	35-39	36-111		53	53-60	55-169	
64 QAM		42	43-48	45-137		65	65-74	68-208	
128 QAM		51	51-58	53-164		78	79-89	82-251	
256 QAM		58	59-67	61-188		89	90-102	94-287	
512 QAM		64	65-73	67-206		98	99-112	103-316	
1024 QAM (Strong FEC)		67	68-77	71-216		104	105-119	109-335	
1024 QAM (Light FEC)		72	72-82	75-230		111	111-126	116-355	
QPSK	14 MHz with XPIC	18	18-21	19-59	20 MHz (No XPIC)	27	28-31	29-88	
8 PSK		28	28-31	29-89		41	41-47	43-132	
16 QAM		38	38-43	40-121		56	57-64	59-180	
32 QAM		50	50-57	53-161		74	75-85	78-238	
64 QAM		62	62-70	65-198		91	92-104	96-293	
128 QAM		75	75-85	78-240		110	111-126	116-354	
256 QAM		86	86-98	90-275		125	126-142	131-401	
512 QAM		97	98-111	102-312		136	137-156	143-438	
1024 QAM (Strong FEC)		105	106-120	110-338		145	146-165	152-466	
1024 QAM (Light FEC)		112	113-128	118-360		154	155-176	162-495	
2048 QAM	N/A	N/A	N/A	164	165-187	172-528			
QPSK	25 MHz (No XPIC)	35	35-40	37-112	25 MHz with XPIC	34	34-39	36-109	
8 PSK		52	53-60	55-168		51	51-58	53-164	
16 QAM		71	72-81	75-229		69	70-79	73-223	
32 QAM		94	95-107	99-302		92	92-105	96-295	
64 QAM		116	117-132	121-372		113	114-129	118-362	
128 QAM		139	141-159	147-448		136	137-156	143-438	
256 QAM		159	160-181	167-511		156	157-178	164-502	
512 QAM		175	177-200	184-564		174	175-198	182-558	
1024 QAM (Strong FEC)		186	188-213	196-599		184	186-210	194-593	
1024 QAM (Light FEC)		198	199-226	208-636		196	197-223	206-629	
2048 QAM	212	214-242	223-682	N/A	N/A	N/A			
QPSK	28 MHz (No XPIC)	40	40-45	42-127	28 MHz with XPIC	39	39-44	41-124	
8 PSK		59	60-68	62-191		58	58-66	61-186	
16 QAM		81	82-93	85-261		79	80-90	83-254	
32 QAM		107	108-122	112-344		104	105-119	109-335	
64 QAM		132	133-150	138-424		128	129-146	135-413	
128 QAM		159	160-181	166-509		155	156-177	163-498	
256 QAM		181	182-206	190-580		177	179-202	186-570	
512 QAM		199	201-227	209-640		197	199-225	207-634	
1024 QAM (Strong FEC)		212	214-242	223-681		210	211-239	220-674	
1024 QAM (Light FEC)		225	227-257	236-723		223	224-254	234-715	
2048 QAM	241	243-275	253-775	N/A	N/A	N/A			
QPSK	30 MHz (No XPIC)	42	42-48	44-135	30 MHz with XPIC	41	41-47	43-132	
8 PSK		61	62-70	64-197		61	62-70	65-197	
16 QAM		86	87-98	90-277		84	85-96	88-270	
32 QAM		113	114-129	119-364		111	111-126	116-355	
64 QAM		140	141-159	147-449		136	137-155	143-437	
128 QAM		168	169-192	176-540		164	166-188	173-528	
256 QAM		193	195-220	203-621		188	190-215	198-604	
512 QAM		206	208-235	216-662		209	211-238	220-672	
1024 QAM (Strong FEC)		225	226-256	236-722		222	224-253	233-714	
1024 QAM (Light FEC)		238	240-271	250-764		236	238-269	248-758	

PTP 820G SPLIT MOUNT SOLUTION SPECIFICATION SHEET

2048 QAM		260	262-296	273-833		N/A	N/A	N/A	
		Ethernet Throughput (Mbps)					Ethernet Throughput (Mbps)		
Modulation	Channel Size	No Compression	L2 Compression	Multi-Layer Compression	Channel Size	No Compression	L2 Compression	Multi-Layer Compression	
QPSK	40 MHz (No XPIC)	57	57-65	60-183	40 MHz with XPIC	55	56-63	58-178	
8 PSK		85	86-97	89-273		83	83-94	87-265	
16 QAM		116	117-132	121-372		112	113-128	118-361	
32 QAM		152	154-174	160-490		148	149-169	156-476	
64 QAM		187	189-214	197-602		182	183-208	191-585	
128 QAM		226	228-258	238-728		220	222-251	231-707	
256 QAM		243	245-278	256-782		237	239-270	249-761	
512 QAM		267	269-304	280-833		273	275-312	287-833	
1024 QAM (Strong FEC)		302	305-345	318-833		297	299-339	312-833	
1024 QAM (Light FEC)		321	324-366	337-833		316	318-360	331-833	
2048 QAM		347	350-396	365-833		N/A	N/A	N/A	
QPSK	50 MHz (No XPIC)	69	70-79	73-223	50 MHz with XPIC	71	71-81	74-228	
8 PSK		108	108-123	113-346		106	107-121	111-340	
16 QAM		146	147-166	153-469		144	145-164	151-462	
32 QAM		183	185-209	193-589		189	191-216	199-609	
64 QAM		237	239-270	249-761		233	234-265	244-747	
128 QAM		276	278-315	290-833		281	283-321	295-833	
256 QAM		327	330-374	344-833		322	324-367	338-833	
512 QAM		355	358-405	373-833		349	352-398	367-833	
1024 QAM (Strong FEC)		387	390-441	406-833		380	383-433	399-833	
1024 QAM (Light FEC)		411	414-468	431-833		403	406-460	424-833	
2048 QAM		443	446-505	465-833		N/A	N/A	N/A	
QPSK	56 MHz (No XPIC)	81	#VALUE!	86-262	56 MHz with XPIC	80	80-91	84-256	
8 PSK		121	122-138	127-390		119	120-136	125-382	
16 QAM		165	166-188	173-531		162	163-185	170-520	
32 QAM		217	219-248	228-699		213	215-243	#VALUE!	
64 QAM		267	269-304	280-833		261	263-298	275-833	
128 QAM		323	325-368	339-833		316	319-361	332-833	
256 QAM		369	372-421	388-833		361	364-412	380-833	
512 QAM		401	404-457	421-833		392	396-448	412-833	
1024 QAM (Strong FEC)		436	439-497	458-833		427	430-487	448-833	
1024 QAM (Light FEC)		462	466-528	486-833		453	457-517	476-833	
2048 QAM		502	505-572	527-833		N/A	N/A	N/A	
QPSK	60 MHz (No XPIC)	86	86-98	90-276	60 MHz with XPIC	84	85-96	88-270	
8 PSK		125	126-143	131-402		125	126-143	131-402	
16 QAM		174	175-198	182-558		170	171-194	179-546	
32 QAM		229	230-261	240-734		224	226-255	235-719	
64 QAM		281	283-320	295-833		275	277-314	289-833	
128 QAM		339	342-387	356-833		332	335-379	349-833	
256 QAM		391	394-447	411-833		380	383-433	399-833	
512 QAM		421	424-480	442-833		412	416-471	433-833	
1024 QAM (Strong FEC)		458	461-522	481-833		449	452-512	471-833	
1024 QAM (Light FEC)		486	490-555	511-833		476	480-543	500-833	
2048 QAM		527	531-601	553-833		N/A	N/A	N/A	